- 1. 1104.1 Keep 48" language from 2009 NCBC
- 2. 1104.2 Keep 48" language from 2009 NCBC
- 3. 1104.3.2 retain the exceptions from the 2009 IBC as they are.
- 4. 1104.4 Exc. 1 1.4 Add: This exception shall not apply to:
 - a. All buildings of state, county, or municipal government or any government agencies, including publicly owned schools, colleges, university buildings, and publicly owned dormitories, two or more stories in height.
- 5. 1107.6.2.1.1 [See changes in text below]
 - a. Change "more than 20" to "11 or more".
 - b. Change 2% to 5%.

The revised text will read as follows:

1107.6.2.1.1 Type A units. In Group R-2 occupancies containing <u>11 or more dwelling units</u> or sleeping units, at least <u>2 5 percent</u> but not less than one of the units shall be a *Type A unit*. For a site with more than 100 units, at least <u>2 percent of the number of units exceeding 100 shall be Type A units</u>. All R-2 units on a site shall be considered to determine the total number of units and the required number of *Type A units*. Type A units shall be dispersed among the various classes of units.

- 7. 1109.4 Add from 2009 NCBC 1109.4 <u>a + b</u> underneath for new <u>a + b</u>.
- 8. 1110.1 Amend 1110.1 as in 2009 NCBC, but correct reference to 20-37.6 [make it a general reference, leaving out (d)]; include 136-30, and the NCDOT reference to the Uniform Manual on Traffic Control Devices [Need to check for correct full name]
- 9. 1106.2 Revise language as follows:
 - a. **1106.2 Groups R-2** and **R-3**. At least 2 percent, but not less than one, of each type of all parking spaces, or a minimum of one space per *Type A dwelling unit*, whichever is larger, shall be provided for occupancies in Groups R-2 and Groups R-3, which are required to have *Accessible, Type A* or *Type B dwelling* or *sleeping units*, shall be *accessible*. Where parking is provided within or beneath a building, accessible parking spaces shall also be provided within or beneath the building.
- 10. 2009 ICC Ch.11 Committee reviewed all 2009 ICC changes within Ch. 11 and elected to make no changes to the 2011 NCBC. All 2009 ICC Ch.11 code changes approved.
- 11. 1106.5 Exc. Accepted
- 12. 3408.4 Was reviewed by BCC ICC Structural Committee no changes recommended.
- 13. Revise 3411.8.8 as follows:

3411.8.8 Type A dwelling or sleeping units. Where 20 11 or more Group R-2 dwelling or sleeping units are being added, the requirements of Section 1107 for Type A units apply only to the quantity of the spaces being added.

14. Appendix E - Adopt everything as written.

1106.2 Groups R-2 and R-3. At least 2 percent, but not less than one, of each type of parking space provided for occupancies in Groups R-2 and Groups R-3, which are required to have *Accessible, Type A* or *Type B dwelling* or *sleeping units*, shall be *accessible*. Where parking is provided within or beneath a building, accessible parking spaces shall also be provided within or beneath the building.

March 8, 2010 Page 1